

海曙科生 超声波细胞破碎仪

名称	产品介绍	型号	频率 KHz	功率 W	变幅杆末端直径可选配 英寸	随机 mm	破碎量 ml
KS-F 型 电脑程控 细胞粉碎机	1. 频率自动跟踪 2. 宽屏液晶显示 菜单式提示 3. 输出振幅 0-100%可调 4. 过温保护 5. 10 操作程序	KS-250F	20	250	1/8 " 1/4 "	1/8 "	0.5~200
		KS-500F		500	1/8 " 1/4 " 3/8 "	1/4 "	0.5~300
		KS-750F		750	1/8 " 1/4 " 1/2 "	1/2 "	0.5~600
		KS-900F		900	1/4 " 1/2 " 9/16 "	1/2 "	20~700
		KS-1200F		1200	1/4 " 1/2 " 9/16 " 3/4 "	3/4 "	20~1000
		KS-1500F		1500	1/4 " 1/2 " 9/16 " 3/4 " 1 "	3/4 "	20~1200
		KS-1800F		1800	1/2 " 9/16 " 3/4 " 1 "	1 "	100~1200
S 型 通用标准 细胞粉碎机	1. 美式控制系统, 有单独脱气功能 2. 最新的球形波 超声清洗机。	KS-130	20	130	1.98, 3.2 (手持式)	Ø1.98	0.5~100
		KS-150		150	1.98, 3.2, 6.3	Ø3.2	0.5~100
		KS-250		250	3.2, 6.3, 9.5	Ø6.3	5~200
		KS-600		600	3.2, 6.3, 12.7	Ø6.3	5~500
		KS-900		900	6.3, 12.7, 14.3	Ø12.7	10~600
		KS-1200		1200	6.3, 12.7, 19	Ø19	10~1000
		KS-1500		1500	6.3, 12.7, 19, 25	Ø19	10~1200
KS-C 型 进口标准 细胞粉碎机	1. 频率自动跟踪输 出振幅0-100% 连续可调; 2. 菜单式提示, 温控检测显示。	KS-250C	20	250	1/8 " 1/4 "	1/8 "	0.5~200
		KS-500C		500	1/8 " 1/4 " 3/8 "	1/4 "	0.5~300
		KS-750C		750	1/8 " 1/4 " 1/2 "	1/2 "	0.5~600
		KS-900C		900	1/4 " 1/2 " 9/16 "	1/2 "	20~700
		KS-1200C		1200	1/4 " 1/2 " 9/16 " 3/4 "	3/4 "	20~1000
		KS-1500C		1500	1/4 " 1/2 " 9/16 " 3/4 " 1 "	3/4 "	20~1200
		KS-1800C		1800	1/2 " 9/16 " 3/4 " 1 "	1 "	100~1200
JY 系列 细胞粉碎机	1. 频率自动跟踪输 出振幅0-100% 连续可调; 2. 菜单式提示, 温控检测显示; 3. 标配隔音箱	JY96-II	20~25	150	0.1, 0.1, 0.2, 0.3	Ø 3 或 Ø 6	10~100
		JY96-II N		150			
		JY88-II		250			
		JY88-II N		250			
		JY92-II		650	0.1, 0.1, 0.2, 0.3, 0.4, 0.5, 0.6	Ø6 或 Ø8	0.5~600
		JY92-II N		650			
		JY92-II D		900			
		JY92-II DN		900			

KS-F 型



KS-C 型



KS / JY 型

